



Type	Resolution	Item	Focal Length	Back Focal Length	Flange Back Length	F No.	Total Track Length	Diameter	Sensing Area	Diagonal	Horizontal	Vertical	Max Image Circle	Mount Type	Composition
BOARD	1.3MP	10620MAS	0.9	2.2	1.00	2.0	16.20	Φ18.40	1/4"(ISX016)	196.00°	190.50°	150.80°	Φ3.7	M10,M12	2G4P
BOARD	1.3MP	12624MAS	1.2	2.0	1.00	2.4	14.00	Φ18.80	1/3.0"	210.00°	192.80°	122.80°	Φ5.5	M10,M12	5G1GM
BOARD	2MP	13620	1.3	2.6	1.80	2.0	16.52	Φ17.00	1/2.8" IMX290 1920*1080 2.9um	200.00°	198.80°	122.40°	Φ5.60	M12	2G4P
BOARD	1.2MP	14620YMAS	1.4	2.9	1.40	2.0	16.77	Φ17.00	1/3" AR0130 (1280*960, 3.75μm)	208.00°	178.00°	138.20°	Φ5.88	∅10	2G4P
BOARD	2MP	14620-2M	1.4	3.1	2.00	2.0	13.00	Φ14.00	1/3.0"	210.00°	180.00°	155.00°	Φ4.40	M12	6G
BOARD	1.2MP	14620	1.4	2.8	2.14	2.0	14.03	Φ14.00	IMX225 1280*960/3.75um	204.00°	191.20°	140.30°	Φ6.00	M12	2G4P
BOARD	VGA	15422AS	1.5	2.4	1.20	2.2	12.00	Φ16.80	1/4.0"	181.40°	139.40°	103.00°	Φ4.48	M10	2G2P
BOARD	1.2MP	16620MAS	1.6	3.3	1.57	2.0	15.66	Φ16.00	1/3" AR0130 (1280*960,3.75μm)	200.00°	172.00°	127.00°	Φ5.50	∅11	2G4P
BOARD	2MP	17620-2MAS	1.7	3.4	1.50	2.0	16.00	Φ17.80	1/2.8"(IMX290)	190.00°	188.60°	102.80°	Φ5.6	M12	4G2P
BOARD	VGA	18513AS	1.8	3.1	2.00	1.3	13.00	Φ13.40	1/4.0"	140.00°	110.00°	84.50°	Φ4.48	M12	3G2P
BOARD	1.3MP	18524MAS	1.8	2.5	1.30	2.4	14.00	Φ18.80	1/3"(AR0132)	177.60°	154.20°	87.00°	Φ5.5	M10,M12	4G1GM
BOARD	VGA	DW2162	2.1	5.7	4.80	2.0	24.40	Φ17.00	1/3.0"	149.20°	117.00°	77.00°	Φ5.20	M12	6G
BOARD	3MP	22724-3MAS	2.2	4.0	3.90	2.0	23.00	Φ27.00	1/2.5"	108.80°	88.80°	85.00°	Φ 5.79	M14	5G2P
BOARD	VGA	DW2425	2.4	4.7	3.80	2.5	18.10	Φ14.00	1/3.0"	163.70°	120.50°	86.90°	Φ6.0	M12	6G
BOARD	3MP	25620-3M	2.5	5.5	5.20	2.0	22.00	Φ17.80	1/2.7"	160.20°	136.50°	73.20°	Φ6.61	M12	6G
BOARD	VGA	26512AS	2.7	4.1	3.00	1.3	17.54	Φ14.00	1/3.2"	109.0°	90.0°	68.4°	Φ5.6	M12	3G2P
BOARD	3MP	29620-3M	2.9	6.3	6.40	2.0	21.50	Φ14.00	1/2.7"	140.50°	119.80°	65.10°	Φ6.61	M12	6G
BOARD	5MP	30620	3.0	6.0	5.08	2.0	22.28	Φ17.00	1/2.7"	140.00°	110.00°	65.00°	Φ7.00	M12	6G
BOARD	5MP	28614-5MAS	3.1	-	5.52	1.4	22.95	Φ14.00	1/2.7"	132.0°	112.0°	60.3°	Φ7.00	M12	2G4P
BOARD	2MP	31420-2M	3.1	6.2	6.20	2.0	22.00	Φ14.80	1/3"(IMX224)	143.90°	100.00°	70.60°	Φ6.0	M12	4G
BOARD	3MP	35619	3.5	5.4	3.00	1.9	16.95	Φ14.00	1/2.44" 1920*1536 3um	130.40°	100.00°	78.00°	Φ7.60	M12	6G
BOARD	2MP	36620	3.6	7.2	5.20	2.0	22.49	Φ14.00	1/2.8"IMX307 1920*1080,2.9um	109.00°	91.00°	49.00°	Φ7.2	M12	6G
BOARD	2MP	40718	4.0	5.2	2.80	1.8	29.04	Φ18.08	1/1.8"SC2210H 1920*1080 4.0um	136.40°	116.00°	62.80°	Φ9.70	M11.42	5G2M
BOARD	2MP	42620	4.2	6.5	4.00	2.0	18.94	Φ14.00	1/2.7" 1920*1080 3um	96.00°	82.50°	45.20°	Φ6.80	M12	6G
BOARD	VGA	DW9707	4.3	6.7	6.22	2.0	22.10	Φ14.80	1/3"	84.10°	65.90°	48.80°	Φ6.00	M12	4G
BOARD	2MP	60516-4MAS	6.0		4.70	1.6	22.50	Φ14.00	1/2.7" 1920*1080, 3μm	67.90°	58.60°	31.70°	Φ6.90	M12	1G4P
BOARD	VGA	DW9607	6.0	6.5	5.90	2.0	15.40	Φ14.00	1/3"	48.90°	39.90°	30.30°	Φ6.0	M12	4G
BOARD	3MP	VIR60620-3M	6.0	7.0	5.40	2.0	21.20	Φ14.00	1/2.7"	64.40°	55.80°	31.00°	Φ6.61	M12	6G
BOARD	VGA	DW62428	6.2	4.5	3.00	2.8	11.50	Φ14.00	1/3.0"	52.30°	43.00°	32.80°	Φ6.00	M12	4G
BOARD	VGA	VIR64425	6.5	9.1	6.24	2.6	12.10	Φ14.00	1/3"	53.40°	42.70°	32.00°	Φ6.0	M12	4G
BOARD	2MP	80660-2M	8.0	7.6	6.50	2.0	24.15	Φ14.00	1/2.7" IMX390 (1936*1216, 3μm)	50.20°	42.20°	26.00°	Φ7.00	M12	6G
BOARD	3MP	VIR80620-3M	8.0	6.3	4.00	2.0	23.20	Φ14.00	1/2.7"	46.30°	40.60°	23.20°	Φ6.61	M12	6G
BOARD	VGA	DW10353	10.3	8.7	6.77	3.0	17.60	Φ14.00	1/2"	43.40°	34.90°	26.50°	Φ10.30	M12	5G
BOARD	VGA	DW9711	16.0	11.8	8.40	2.5	22.20	Φ14.00	1/3"	21.10°	17.00°	12.80°	Φ6.0	M12	3G
BOARD	VGA	DW25425	24.7	12.2	8.10	2.5	29.20	Φ25.00	2/3"	25.20°	20.20°	15.20°	Φ11.0	M12	4G
BOARD	VGA	DW350420	35.0	19.3	15.80	2.0	40.40	Φ25.00	2/3"	17.90°	14.40°	10.80°	Φ11.0	M12	4G
BOARD	VGA	DW500425	50.0	33.8	4.00	2.5	56.80	Φ27.00	1/2.0"	9.16°	7.30°	5.50°	Φ10.30	M12	
PINHOLE	VGA	DW33524-K	3.3	3.4	3.50	2.4	12.20	Φ2.50	1/3"	128.00°	83.00°	57.10°	Φ6.0	M12	5G
PINHOLE	VGA	DW9702	3.4	3.8	2.04	3.5	6.64	M12	1/3"	108.40°	84.80°	63.00°	Φ6.0	M12	1G
PINHOLE	VGA	DW9802	3.7	3.6	3.27	2.0	10.60	Φ8.10	1/3"	96.70°	69.80°	36.50°	Φ6.0	M8	4G
PINHOLE	VGA	DW9803	4.2	3.7	3.72	2.0	10.20	Φ2.30	1/3"	104.10°	73.34°	52.10°	Φ6.0	M12	3G1P
VARIFOCAL	1.3MP	VIR36160MAS	3.6~16.0	6.2~16.1	5.57	1.2~360	12.00	Φ28.40	1/3"	96.6 ~ 56.6	73.4 ~ 20.4	53.3 ~ 15.3	Φ6.1	M14	7G1GM
VARIFOCAL	3MP	60500-3MAS	6.0~50.0	5.8~5.9	13.90	1.6~360	54.40	Φ29.00	1/2.7"	65.9 ~ 7.9	55.7 ~ 6.9	30.0 ~ 3.9	Φ6.61	M14	8G2GM